



Designed to face the challenges of construction in urban and remote areas.

These pumps, mounted on the small versatile chassis trucks, represent the last innovation in efficiency and autonomy.

Gives you the necessary agility to handle in urban environments.

Despite its compact size, it can reach remote places, thanks to its agility and robust design, capable of adapting to all types of driveways. ensuring that you will reach any workplace without difficulty.

The City's pump electronic interface, has been optimized to offer ease of use without complex learning curves.

Its intuitive and robust design makes operation easy, allowing users to get up and running quickly.

This series of pumps complies with all European regulations, guaranteeing viable, sustainable and environmentally friendly work, without loss of productivity, consistency and efficiency in its performance.

With an innovative design for versatility, durability and eco-friendliness, the City is the ideal solution for urban projects and remote environments.

UF CITY PUMPS RANGE

DATA SHEET

UF 100 CITY

UF 130 CITY

RENDIMIENTOS

Maximum volume output*

70m3/h- 100yards3/h

90 m3/h

Maximum concrete pressure

61/91bar- -1030/1540psi

71/106 bar

Maximum aggregate size

38mm- 1.5"

1.5" 38mm

Hydraulic pump

Kawasaki 140cc

Kawasaki 140cc

High and low pressure

High and low pressure

High and low pressure

Hydraulic circuit

Open

Open

Delivery distance :

* (300m)- 330 yards

* (500m)

* Horizontal

* Vertical

(150m)

Delivery distance :

* (100m)- 110 yards

200x1000 mm

Pumping cylinders

200x1000 mm

200x1400 mm

Diameter of hydraulic cylinder

110x63 mm

110x63 mm

Maximum strokes per minute

27/18

25/17

Variable volume control

From 0 to full load

From 0 to full load

Diameter of S-valve

200x150 mm

200x150 mm

Number of shift cylinders

2

2

Hydraulic tank capacity

170 L

170 L

Hopper height

1360 mm

1360 mm

Hopper capacity

500 L

600 L

Outlet diameter

6"-150mm

6"- 150mm

ENGINE

Manufacturer's model

Kohler KDI TCR 2504E5/26

Kohler KDI TCP 3404 E5/22

Water-cooled

Water-cooled

Water-cooled

Horsepower

74 HP 55.4kW @ 2600rpm

141 HP 105kW @ 2200 rpm

Fuel tank capacity

90 L

105L

Axel

2

2

Axle support capacity

5.1 Tn/9.3Tn Max:13 Tn

8Tn/11.5-11.5Tn Max 26 Tn

Ruedas - capacidad de carga

By air

By air

Brakes

Hidráulicas

Hidráulicas

Patas estabilizadoras

DIMENSIONS

Length

8m

10m

Width

2.45m

2.45m

Height

3.7m

3.7m

Weight (approx.)

9 Tn

18 Tn

* Pumping distance, always depends on the type of materials used, humidity, temperature, etc.

FOR + INFORMATION

WWW.UTIFORMEUROPA.COM